

Three

10kW

Solis Three PV Inverter

- ▶ Three phase output
- ▶ Precise MPPT algorithm
- ▶ Compact and light design, easy installation
- ▶ IP65 rated for outdoor installation
- ▶ RS485, WiFi/GPRS (optional) interface
- ▶ WiFi and monitoring app available
- ▶ Numerous protection functions
- ▶ 5 years standard warranty, 20 years optional upgrade



Model:

Solis-10K

Features:

Fanless
Cooling
Concept

Ultra wide
Voltage
Range

WiFi/GPRS
Real time
monitoring

Available on the iPhone
App Store
Available on the iPhone
App Store

IP65

Weight
29kg

Datasheet

Model	Solis-10K
Energy Source	PV
Input Side(DC)	
Max. DC input power(kW)	11.5
Max. DC input voltage(V)	1000
Start-up voltage(V)	250
MPPT voltage range(V)	200-800
Max. input current(A)	18A+18A
MPPT number/Max input strings number	2/4
Output Side (AC)	
Rated output power(kW)	10
Max. apparent output power(kVA)	11
Max. output power(kW)	11
Rated grid voltage(V)	400
Grid voltage range(V)	313-470
Rated grid frequency(Hz)	50/60
Operation phase	Three
Rated grid output current(A)	14.4
Max. output current(A)	16.7
Power Factor (at rated output power)	0.8...1...0.8
THDi (at rated output power)	<3%
DC injection current(mA)	<20
Grid frequency range(Hz)	47-52 or 57-62
Efficiency	
Max. efficiency	98.2%
EU efficiency	97.3%
MPPTefficiency	>99.5%
Protection	
DC reverse-polarity protection	Yes
Short circuit protection	Yes
Output over current protection	Yes
Output over voltage protection	Yes
Insulation resistance monitoring	Yes
Residual current detection	Yes
Surge protection	Yes
Islanding protection	Yes
temperature protection	Yes
Integrated DC switch	Optional
General Data	
Dimensins(mm)	430W*613H*269D (mm)
Weight(kg)	29
Topology	Transformerless
Self consumption (night)	<1W(Night)
Operating ambient temperature range	-25~60°C
Ingress protection	IP65
Noise emission{typical}	<30 dBA
Cooling concept	Natural convection
Max.operation altitude	4000m
Designed lifetime	>20years
Grid connection standard	EN50438, G59/3, AS4777, VDE0126-1-1, IEC61727
Relative humidity	0~100%
Safty/EMC standard	IEC62109-1/-2, AS3100, EN61000-6-1, EN61000-6-3,
Features	
DC connection	MC-4mateable
AC connection	IP67rated plug
Display	LCD,2×20 Z.
Communication connections	4 pins RS485 connector
Warranty	5 years standard (extend to 20 years)